

## FS-16G-4X-GPON-L3-DP



### Product Overview:

The FS-16G-4X-L3-DP is a pizza-box GPON OLT with 16 GPON ports that meets flexible and fast FTTx access, suiting the scenarios such as sparse/ remote/cost-sensitive area, smart industrial park, commercial building and FTTM, etc.

### Highlights

- **Compact design, meets various application scenarios**

Supports the deployment in diverse scenarios including low density areas, remote areas, sparsely-populated areas and industry parks.

Supports FTTM and sharing site/rack with wireless base stations.

- **Small size and lightweight, easier to delivery and install**

Small size and lightweight, easy to transport and install.

Supports multiple installation modes, like limited room space, basement, low-voltage room and small rack or cabinet.

- **Carrier-class security protection, support dynamic routing protocol RIP&OSPF, ensure the safe operation of network**

Supports uplink redundancy protection including LACP STP, RSTP and MSTP, and support RIP&OSPF protocol Supports link protection.

- **Lower TCO**

Dramatically saves on investment fees in trunk fibers, pipe engineering, and facilities. Effectively reduce CapEx and OpEx.

### Technical Specifications

Item		FS-16G-4X-GPON-L3-DP
Chassis	Rack	1U 19Inch Standard Box
GE/10GE Uplink Port	QTY	8
	RJ45(GE)	4
	SFP(GE)/SFP+(10GE)	4
GPON Port	QTY	16
	Physical Interface	SFP Slots
	Connector Type	Class (Class C++/Class C+++)
	Max splitting ratio	1:128
Management Ports		1*10/100/1000BASE-T out-band port, 1*CONSOLE port, 1*USB2.0, 1*Type-C USB (for console)
PON Port Specification (Class C+++module)	Transmission Distance	20KM
	GPON port speed	Upstream 1.244Gbps, Downstream 2.488Gbps
	Wavelength	TX 1490nm, RX 1310nm
	Connector	SC/UPC
	Fiber Type	9/125μm SMF
	TX Power	+4.5~+10dBm
	Rx Sensitivity	≤ -30dBm
Saturation Optical Power	-12dBm	
Management Mode		EMS, TR069 VACS, WEB, SNMP, Telnet , CLI

**Management Function**

- SNMP,Telnet,CLI,WEB,SSH v2;
- Fan Group Control
- Port Status monitoring and configuration management
- Online ONTconfiguration and management
- User management
- Alarm management

**Layer2 Switch**

- 32K Mac address
- Support 4096 VLANs
- Support port VLAN and protocol VLAN
- Support VLAN tag/Un-tag, VLAN transparent transmission
- Support VLAN translation and QinQ
- Support storm control based on port
- Support port isolation
- Support port rate limitation
- Support 802.1D and 802.1W
- Support static LACP,Dynamic LACP
- QoS based on port, VID, TOS and MAC address
- Access control list
- IEEE802.x flowcontrol
- Port stability statistic and monitoring

**Multicast**

- IGMP snooping
- 2048 IP Multicast Groups;

**DHCP**

- DHCP server,DHCP relay,DHCP snooping
- DHCP option82

**Layer 3 Route**

- ARP proxy
- 4096 hardware Host Routes512 hardware Subnet Routes
- Support 802.1X,Radius,Tacacs+
- Support IP source guard
- Support static route ,dynamic route RIP v1/v2,RIPngand OSPF v2/v3;

**IPv6**

- Support NDP;
- Support IPv6 Ping,IPv6 Telnet,IPv6 routing;
- Support ACL based on source IPv6 address, destination IPv6 address, L4 port, protocol type, etc;
- Support MLD v1/v2 snooping(Multicast Listener Discovery snooping)

**GPON Function**

- Tcont DBA
- Gempport traffic
- In compliant with ITU-T984.x standard
- Up to 20KM transmission Distance
- Support data encryption, multi-cast, port VLAN, separation, RSTP, etc
- Support ONT auto-discovery/link detection/remote upgrade of software

- Support VLAN division and user separation to avoid broadcast storm
- Support power-off alarm function, easy for link problem detection
- Support broadcasting storm resistance function
- Support port isolation between different ports
- Support ACL and SNMP toconfigure data packet filter flexibly
- Specialized design for system breakdown prevention tomaintain stable system
- Support RSTP,IGMP Proxy

**Dimension (L\*W\*H)**

- 442mm\*320mm\*43.6mm

**Weight**

- Net weight of single power 4.80kg
- Gross weight of single power 6.40kg

**Power Consumption**

- 85W

**Working Temperature**

- 0°C ~+50°C

**Storage Temperature**

- -40~+85°C

**Relative Humidity**

- 5~90% (non-conditioning)

**Ordering Information:**

Product Name	Product Description	Power Configuration	Accessories
FS-16G-4X-GPON-L3-DP	16*GPON,4*RJ45+4*SFP/SFP+	1*AC power 2*AC power 2*DC power 1*AC power + 1* DC power	GPON SFP C++ module GPON SFP C+++ module 1G SFP module 10G SFP+ module