

## FibRSol- FTTX Router - 1 GE Port

Model: FS-1GE

### Highlights:

- ✓ Dual Mode
- ✓ LAN
- ✓ FTTX
- ✓ QOS
- ✓ AUTO MDIX
- ✓ Plug and Play



### Product Overview:

FibRSol FS-1GE dual mode client router is the Gigabit router. It has high stability and easy to maintain, has multi-service QoS quality guarantee. And It is fully compliant with technical regulations and technical requirement of Equipment (V2.1 and above version) and comply with IEEE802.3ah, meet the "YD/T 1475-2006 access network technical requirements of "the Telecom equipment technical requirements" for network equipment. It is a small-capacity router which can well meet the application of FTTX network. Efficient bandwidth utilization and Ethernet service support capabilities help operators deliver reliable service quality assurance to their customers.

### Features:

- ✓ Auto-adaptive to the network;
- ✓ Plug and Play, integrate auto detection, auto configuration and auto firmware upgrading;
- ✓ Support diagnostic monitoring and remote disabling;
- ✓ Full speed 1G non-blocking ;
- ✓ 2048 MAC address table;
- ✓ integrated port monitoring, port mirroring, port rate limiting, port SLA, etc.
- ✓ Support auto polarity detection of Ethernet ports (AUTO MDIX);
- ✓ Integrated IEEE802.1p QoS with four level Priority queues;
- ✓ Supports mixed network with mainstream minimize operators' network construction costs;
- ✓ With the industry's advanced technology, it has powerful functions and QoS guarantees in Ethernet service;
- ✓ Desktop devices take up less space and consume less power.

## Hardware Spec

**Dimension:**

100\*65\*20mm (length\*width\*height)

**Net weight:** ≤0.1Kg

**Fiber Port:**

- (i) Auto-adaptive interface, SC single- mode/single fiber,
- (ii) Work as , downstream rate 2.5Gbps, Upstream rate 1.25Gbps
- (iii) Work as , downstream rate 1.25Gbps, Upstream rate 1.25Gbps

**Wavelength:**

Tx 1310nm, Rx 1490nm

**Storage:**

Storage Temperature: -30℃ ~ +60℃

Storage Humidity: 10~90% (non-condensation)

## Software Spec

**Fiber interface:** SC/PC

**RX sensitivity:** <-28dBm (1490nm)

**LAN:** 1\*10/100/1000Mbps adaptive Ethernet ports, Full/half duplex, RJ45 interface

**Throughput:** Throughput can reach 900Mbps or more

**DC Power:** 5V 1A, external AC-DC Power Adapter

**Button:** Reset, power

**Power:** ≤8W

**Operation:** Working temperature: -5~+55℃  
Working humidity: 10~90% (non-condensation)



## Ordering Information:

Model	Description
FS-1GE	1 x Gigabit, 1WAN Port Plastic Case with Routing